



US007295872B2

(12) **United States Patent**
Kelly et al.

(10) **Patent No.:** US 7,295,872 B2
(45) **Date of Patent:** Nov. 13, 2007

(54) **SYSTEM FOR AND METHOD OF POWER EFFICIENT ELECTRICAL TISSUE STIMULATION**

(75) Inventors: **Shawn Kelly**, Cambridge, MA (US); **Joseph Rizzo**, Boston, MA (US); **John Wyatt**, Sudbury, MA (US)

(73) Assignee: **Massachusetts Institute of Technology**, Cambridge, MA (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 669 days.

(21) Appl. No.: **10/267,764**

(22) Filed: **Oct. 9, 2002**

(65) **Prior Publication Data**

US 2003/0130699 A1 Jul. 10, 2003

Related U.S. Application Data

(60) Provisional application No. 60/328,346, filed on Oct. 10, 2001.

(51) **Int. Cl.**
A61N 1/18 (2006.01)

(52) **U.S. Cl.** **607/2; 607/4; 607/9; 607/34;**
607/53; 607/61

(58) **Field of Classification Search** **607/34,**
607/36, 33, 61, 2, 4-5, 9, 13, 53
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,082,097 A	4/1978	Mann et al.
4,114,627 A	9/1978	Lewyn et al.
4,399,818 A	8/1983	Money
4,596,252 A *	6/1986	Nelson
4,628,933 A *	12/1986	Michelson
		607/9
		607/53

5,312,439 A	5/1994	Loeb
5,522,865 A	6/1996	Schulman et al.
5,876,425 A	3/1999	Gord et al.
6,035,237 A	3/2000	Schulman et al.
6,181,969 B1	1/2001	Gord et al.
6,415,186 B1	7/2002	Chim et al.
2002/0068957 A1	6/2002	Wolfe et al.

OTHER PUBLICATIONS

"A Neuro-Stimulus Chip with Telemetry Unit for Retinal Prosthetic Device" by Liu, et al., IEEE Journal of Solid-State Circuits, vol. 35, No. 10, Oct. 2000.

WIPO Publication No. WO 03/030991 A1 entitled "Power Saving System for Neural Implant Devices" by Wyatt, et al., dated Apr. 17, 2003.

International Search Report Re: PCT/US02/32509, filed Oct. 10, 2002.

* cited by examiner

Primary Examiner—Robert Pezzuto

Assistant Examiner—Shevon Johnson

(74) **Attorney, Agent, or Firm**—Sam Pasternack; Choate Hall & Stewart LLP

(57) **ABSTRACT**

Circuitry for and method of power efficient operation of, and energy recovery from, tissue-stimulating electrodes having high charge capacities. Post-stimulation energy is recovered from the electrodes through a variety of techniques into circuit elements such as other electrodes, an intermediate distribution system, a power supply or any other elements, through the use of sequential switching. Energy is also recoverable from the intermediate distribution system, which preferably is comprised of one or more storage capacitors operating a different voltages. Efficient power transfer among circuit elements is effected by transferring energy while limiting element-element voltage differences and/or voltage differences between the elements and the capacitances of the electrodes.

3 Claims, 11 Drawing Sheets

