

Individual Lab Report 1



Lunar ROADSTER

Team I

Author: **Boxiang (William) Fu**
Andrew ID: boxiangf
E-mail: *boxiangf@andrew.cmu.edu*

Teammate: **Deepam Ameria**
ID: damera
E-mail: *damera@andrew.cmu.edu*

Teammate: **Bhaswanth Ayapilla**
ID: bayapill
E-mail: *bayapill@andrew.cmu.edu*

Teammate: **Simson D'Souza**
ID: sjdsouza
E-mail: *sjdsouza@andrew.cmu.edu*

Teammate: **Ankit Aggarwal**
ID: ankitagg
E-mail: *ankitagg@andrew.cmu.edu*

Supervisor: **Dr. William "Red" Whittaker**
Department: Field Robotics Center
E-mail: *red@cmu.edu*

February 14, 2025

1 Individual Progress

1.1 Sensors and Motor Control Lab

I was responsible for developing and integrating a standalone graphical user interface (GUI) for the sensors and motor control lab. The GUI was done using the Qt Creator toolkit with customized packages 'Q Custom Plot' for plotting the transfer function and 'Q Serial Port' for interfacing with an Arduino Due via serial port. Figure 1 displays the layout of the GUI.




Figure 1: GUI Layout

The 'Motor Control' panel controls the 3 motors given out for the lab. The RC servo motor is controlled by a slider with a range between 0 to 180 degrees to control its desired angle. The stepper motor is controlled by a slider with a range between -180 to 180 degrees to control its desired angle. A switch button is used to change motor control between the GUI and the potentiometer. The DC motor is controlled by two text boxes. When velocity control is desired, the velocity text box is used to control the RPM of the DC motor within the range of -118 to 118 RPM. When position control is desired, the angle slider is used to control the angle in degrees of the DC motor within the range of -360 to 360 degrees from its current angle. Negative values switch the motor's direction of rotation. The terminal values of each motor's range is determined from the specification sheets of the motors given to us.

Once the GUI detects a change in the control values, it calls the `{Motor}_valueChanged` function. After converting the slider value to a predetermined format that is readable by the microcontroller, it is passed through the serial port to the Arduino Due. Once the command reaches the Arduino, it runs through the `handleCommand` function to determine which motor controller to send the command to. It then calls the appropriate motor controller function `{Motor}Controller` along with the passed value. The baton is then passed to my teammates to implement the inner workings of the motor controller function of their designated motor.

On the right side of the 'Motor Control' panel, the state of the motor is displayed via a LCD number. This display, along with the 'Sensor Readings' panel, are updated with a state callback function called at 5 Hz. Every 0.2 seconds, the GUI sends a request to the Arduino for its motor and sensor states. The Arduino then calls `{Motor}StateCallback`

for each motor and {Sensor}Callback for each sensor. The inner workings of each callback function was done by my teammates. Finally, the callback returns are concatenated and sent to the GUI in a predetermined format. The GUI back-end unpacks this and displays the values on the interface.

At the bottom of the GUI, a transfer function plot is displayed. It plots the input voltage of an ultrasonic range finder on the x-axis and the physical distance between the sensor and the detected object in centimeters on the y-axis. The plotter function was done by me using the 'Q Custom Plot' extension. The values feeding into the plot was completed by my teammate Bhaswanth. The completed physical system is shown in Figures 2 and 3.




Figure 2: Sensors & Motor Control Lab Physical Setup




Figure 3: Close-up of Breadboard Setup

1.2 MRSD Project

Since the submission of the Conceptual Design Review Report, I have worked on the following tasks on the MRSD project:

1.2.1 Teleoperation of the Rover

The software stack left by the previous MRSD team Crater Grader already had a teleoperation stack to control the rover using a joystick. However, the documentation of how to use it is poor and outdated (e.g., the documentation specified to use the launch file `joystick_launch.py` where instead `motion_control_launch.py` should be used). I spent the majority of the winter break documenting Crater Grader's teleoperation stack and updating it to ROS2 Humble and Ubuntu 22.04. The updated documentation can be seen in Figures 4 and 5.

Lunar ROADSTER & Crater Grader Docker Bringup

The docker image is contained within the USB attached to the Jetson. The following procedure should be followed to obtain access to the Crater Grader docker container:

1. `sudo chmod 755 /usb /sd_card`
2. Type `df -h` to find mounting port of the USB drive. It should be `/dev/sda1` or `/dev/sdb1`
3. `sudo mount /dev/sda1 /usb` (replace with `/dev/sd{Port}1` if it is mounted elsewhere. You should see `CRATER_GRADER` under `ls`, if not `cd ..` and then `cd /usb` back)
4. `sudo mount /dev/mmcblk1p1 /sd_card`
5. Go inside `cd /sd_card`
6. `sudo systemctl restart docker` (you might need to rerun `sudo chmod 755 /usb /sd_card` if permissions are revoked)
7. `sudo docker start -i lunar_roadster_dev_jetson`
8. To open a new terminal: `sudo docker exec -it lunar_roadster_dev_jetson zsh`
9. For CraterGrader:
 - a. Go inside `/usb : docker-compose up -d cg-dev-hw`
 - b. Go inside `cd ./scripts`
 - c. `source set-udev-rules.sh`
 - d. `docker-compose exec cg-dev-hw zsh`
 - e. You should now be inside Crater Grader docker and see their logo
 - f. `source ./install/local_setup.zsh`
 - g. Make sure the directory `/dev/cg_dev` is present and contains `tty_arduino`. This is the hardware interface from inside the docker to the Jetson.

Connecting Additional Terminals to the Docker

1. `cd /usb/CRATER_GRADER/`
2. `docker-compose exec cg-dev-hw zsh`
3. `source ./install/local_setup.zsh`
4. If it says `zsh: corrupt history file /root/.zsh_history` copy and paste Step 3 again

Figure 4: Documentation of Crater Grader's Docker

1.2.2 Moon Pit Crater Distribution

Adhering to advice by our supervisor, we adapted the crater generation code from the Moonshot Circumnavigating team to our needs. This involves reading in a dataset of the number of craters and its diameter. Fitting it to a Log-Log probability distribution, and sampling from the distribution for a 6 meter by 6 meter area that mimics the size of the moon pit in the Planetary Robotics Lab. The purpose of this task is to generate a landscape in the moon pit that has a crater distribution that is relatively lunar-realistic.

Crater Grader Teleop Bringup

1. Open at least 2 terminals connected to the docker
2. `source ./install/local_setup.zsh` on all terminals
3. Check if the LEDs on the RoboClaws (RC1, RC2, and RC3) are flashing green. If not, press the **Reset** button on the Arduino
4. `colcon build` if not already built, then `source ./install/local_setup.zsh` again if needed
5. `ros2 launch motion_control motion_control_launch.py`
6. Use the other terminal and change the `mux_mode` to `teleop` using `ros2 topic pub /mux_mode cg_msgs/msg/MuxMode "{mode: 3}" --once`
7. You should be able to teleop the rover now. If not, check debugging section below

Checking if Gadgets and Links are Functioning Properly (for Teleop)

The following topics should be publishing messages if the links and gadgets are functioning properly:

- Joystick to Jetson: `ros2 topic echo /joy`
- Jetson to Arduino Interface: `ros2 topic echo /teleop_cmd`
- Arduino Interface to Arduino: `ros2 topic echo /arduino_cmd`
- Arduino to Jetson: `ros2 topic echo /arduino_feedback`

One common issue that we found was that the `micro_ros_agent` was not being initialized properly. A potential checklist to solve this is as follows:

1. `source install/local_setup.zsh`
2. `ros2 run micro_ros_setup create_agent_ws.sh`
3. `ros2 run micro_ros_agent micro_ros_agent serial --dev /dev/cg_dev/tty_arduino -v6`
4. If the logger is not showing info, press the reset button on the Arduino. You should see `recv_message` and `send_message` if the `micro_ros_agent` is set up properly.

Figure 5: Documentation of Crater Grader's Teleoperation Stack

This aids in guiding how we should implement our algorithms for path planning and tool planning. An example of the generated moon pit is shown in Figure 6.




Figure 6: Moon Pit Crater Generation

1.2.3 ZED 2i Depth Camera Setup

With the help of my teammate Bhaswanth, I have set up the ZED 2i depth camera that our rover will use for localization and validation. This includes installing NVIDIA

CUDA drivers and the ZED SDK drivers into our docker environment. It also involves interfacing the ZED camera and the docker container via serial port (i.e., so the data stream can be read inside the container), and converting the data stream to video using OpenCV. The video from the ZED camera will be used subsequently for the localization and validation stacks later on in our project.

1.2.4 LAN Setup

I have set up a private LAN network for communications between devices. This is because prior MRSD teams had problems using the CMU-Secure network to transmit data during periods of high user traffic (e.g., SVD and FVD when 50+ people connect to the same WiFi port). The LAN network is connected to the internet via a wall outlet near our lab. We will be using the private network to establish communication between the rover's NVIDIA Jetson computer and the operations terminal on our laptops. Additionally, we will be using the private network to relay position information from the total station to the Jetson via a TX2 chip located beside the moon pit. Finally, static IPs were set on the private network so the connection port via `ssh` and Remmina does not change daily.

2 Challenges

2.1 Sensors and Motor Control Lab

One major challenge I faced when developing the GUI was that the serial port returns from the Arduino are best-effort delivery and not guaranteed delivery. This means that the return deliveries could be cut or that several returns could be bundled together in a single delivery. To fix this problem, I followed the solution from [this](#) repository. Essentially, it involves creating a serial buffer that waits until at least 2 returns are read. It discards the first return since it may be missing the front part of the message. The second message is used after checking that the message is of the correct length (so no lost packets occurred).

2.2 MRSD Project

The biggest challenge I faced for the MRSD project was getting Crater Grader's teleoperation stack to work. This is because the teleoperation README file that they provided was outdated and incorrect. I spent several days going through their code to understand how the ROS2 nodes were related. I found that there was a missing link between the `/teleop_cmd` topic from the joystick controller and the `/arduino_cmd` topic that was sending information to the Arduino and RoboClaw microcontrollers. The link was not inside the `src/teleop` directory but instead in the `src/motion_control` directory. After figuring this out, I was able to locate the correct launch file that links all the teleoperation nodes up. However, the rover was still not moving despite the `/arduino_cmd` topic pushing commands. It took some more time to figure out that the `mux_mode` of the rover needs to be changed from autonomous to teleoperation. This is done through the command `ros2 topic pub /mux_mode cg_msgs/msg/MuxMode "{mode: 3}" --once`. Only after this step was I able to get the rover to move based on teleoperation commands.

3 Teamwork

A breakdown of the contributions of each team member are tabulated below:

3.1 Sensors and Motor Control Lab

- **Ankit Aggarwal:** Implemented the stepper motor speed and direction controller using a potentiometer.
- **Deepam Ameria:** Interfacing IMU sensor and servo motor controller.
- **Bhaswanth Ayapilla:** Interfacing Ultrasonic Range Finder, implementing median/mode filter and transfer function, README file for the complete code.
- **Simson D'Souza:** Implemented DC motor control with encoder feedback and interfaced an IR sensor for distance measurement.

3.2 MRSD Project

- **Ankit Aggarwal:** Wheel design and printing, rover hardware setup/maintenance, circuit diagram design (in collaboration with Simson), VectorNav IMU interfacing, preliminary testing (in collaboration with team), project manager.
- **Deepam Ameria:** Prototype dozer development (in collaboration with Simson), preliminary tests for teleoperation and grading with prototype dozer (in collaboration with Simson), dozer blade and mechanism design, FARO scanner setup and Moon Pit scanning (in collaboration with team).
- **Bhaswanth Ayapilla:** NVIDIA Jetson setup, setup encoder drivers, setting up teleoperation (in collaboration with William), ZED Camera setup (in collaboration with William), setting up operations terminal, FARO scanner setup and Moon Pit scanning (in collaboration with team).
- **Simson D'Souza:** Prototype dozer development (in collaboration with Deepam), preliminary tests for teleoperation and grading with prototype dozer (in collaboration with Deepam), circuit diagram design (in collaboration with Ankit), FARO scanner setup and Moon Pit scanning (in collaboration with team), processing of point cloud data to generate an occupancy grid map for navigation.

4 Plans

4.1 Sensors and Motor Control Lab

Currently, there are no future plans for the sensors and motor control lab as it is an auxiliary assignment not directly related to our MRSD project. However, we swapped the motor driver and encoder given to us for the lab with a similar one that we are using for our rover. We also swapped the Arduino UNO with an Arduino Due as it is the microcontroller we plan on using for motor controls on our rover. We hope that the increased knowledge from the lab will be transferrable to our MRSD project and help us integrate our motor control stack.

4.2 MRSD Project

From now until the next lab demo, we hope to finish the hardware of our rover and complete the localization stack in the moon pit. My individual plan is to complete the localization stack with my teammate Bhaswanth. For positional localization, this involves setting up the total station, relaying the total station data via serial port to the TX2 chip beside the moon pit, and transmitting the data via our LAN network to the Jetson on the rover. For orientation localization, this involves reading the IMU data through serial port and extracting its roll, pitch, and yaw. Additionally, the depth camera may give additional data entries for stereo camera localization. The plan is to have the datasets fused together and the rover localized through an Extended Kalman Filter.

5 Code for Sensors & Motor Control Lab Interface

5.1 GUI

I was responsible for coding the entirety of this section except for the filtering of the ultrasonic sensor. The `dialog.ui` script is made with the help of Qt Creator.

5.1.1 main.cpp

```
1 #include "dialog.h"
2 #include "qcustomplot.h"
3
4 #include <QApplication>
5
6 int main(int argc, char *argv[])
7 {
8     QApplication a(argc, argv);
9     Dialog w;
10    w.setFixedSize(940, 850);
11    w.setWindowTitle("Sensors_&_Motor_Lab_Controller");
12    w.show();
13    return a.exec();
14 }
```

Listing 1: main.cpp

5.1.2 dialog.h

```
1 #ifndef DIALOG_H
2 #define DIALOG_H
3
4 #include <QDialog>
5 #include <QSerialPort>
6 #include <QSerialPortInfo>
7 #include <QDebug>
8 #include <QtWidgets>
9
10 QT_BEGIN_NAMESPACE
11 namespace Ui {
12 class Dialog;
13 }
14 QT_END_NAMESPACE
15
16 class Dialog : public QDialog
17 {
18     Q_OBJECT
19
20 public:
21     Dialog(QWidget *parent = nullptr);
22     ~Dialog();
23
24 private slots:
25
26     void updateArduino(QString);
```

```

27
28     void readSerial();
29
30     void on_servo_slider_valueChanged(int value);
31
32     void on_stepper_slider_valueChanged(int value);
33
34     void on_stepper_mode_button_toggled(bool checked);
35
36     void parseCallbackCommands(QString command);
37
38     void updatePlot();
39
40     int filterMean(std::vector<int>&);
41
42 private:
43     Ui::Dialog *ui;
44     QSerialPort *arduino;
45
46     // Arduino Due setup
47     static const quint16 arduino_due_vendor_id = 9025;
48     static const quint16 arduino_due_product_id = 61;
49     QString arduino_port_name;
50     bool arduino_is_available;
51
52     QByteArray serialData;
53     QString serialBuffer;
54     QString parsed_data;
55
56     QTimer *dataTimer;
57     QVector<double> xData, yData;
58
59     double transferFunctionInput;
60     double transferFunctionOutput;
61
62     void onDCPosCommentSubmitted();
63     void onDCVelCommentSubmitted();
64
65     std::vector<int> ultrasonicReadings;
66 };
67 #endif // DIALOG_H

```

Listing 2: dialog.h

5.1.3 dialog.cpp

```

1  /*
2  The following starter template is adapted from the following repos,
   which is under a GNU GPLv3.0 license:
3  https://github.com/vannevar-morgan/Qt-RGB-LED
4  https://github.com/vannevar-morgan/Qt-Temperature-Sensor
5  */
6
7  #include "dialog.h"
8  #include "ui_dialog.h"

```

```

9  #include "qcustomplot.h"
10
11 #include <QSerialPort>
12 #include <QSerialPortInfo>
13 #include <QDebug>
14 #include <QtWidgets>
15
16 #include <vector>
17
18 #include <iostream>
19
20 Dialog::Dialog(QWidget *parent)
21     : QDialog(parent)
22     , ui(new Ui::Dialog)
23 {
24     ui->setupUi(this);
25
26     arduino_is_available = false;
27     arduino_port_name = "";
28     arduino = new QSerialPort(this);
29
30     serialBuffer = "";
31     parsed_data = "";
32
33     transferFunctionInput = 0;
34     transferFunctionOutput = 0;
35
36     // Initialize transfer function plot
37     QCustomPlot *plot = ui->transferFunctionPlot;
38     plot->addGraph();
39
40     plot->xAxis->setLabel("Input_Voltage(V)");
41     plot->yAxis->setLabel("Output_Reading(cm)");
42
43     plot->xAxis->setRange(0, 5);
44     plot->yAxis->setRange(0, 1000);
45
46     dataTimer = new QTimer(this);
47     connect(dataTimer, &QTimer::timeout, this, &Dialog::updatePlot);
48     dataTimer->start(100);
49
50     connect(ui->dc_angle_textbox, &QLineEdit::returnPressed, this, &
        Dialog::onDCPosCommentSubmitted);
51     connect(ui->dc_vel_textbox, &QLineEdit::returnPressed, this, &
        Dialog::onDCVelCommentSubmitted);
52
53     /*
54     // Finds product and vendor ID of Arduino Due
55     qDebug() << "Number of available ports: " << QSerialPortInfo::
        availablePorts().length();
56     foreach(const QSerialPortInfo &serialPortInfo, QSerialPortInfo::
        availablePorts()){
57         qDebug() << "Has vendor ID: " << serialPortInfo.
            hasVendorIdentifier();
58         if(serialPortInfo.hasVendorIdentifier()){

```

```

59         qDebug() << "Vendor ID: " << serialPortInfo.
            vendorIdentifier();
60     }
61     qDebug() << "Has Product ID: " << serialPortInfo.
        hasProductIdentifier();
62     if(serialPortInfo.hasProductIdentifier()){
63         qDebug() << "Product ID: " << serialPortInfo.
            productIdentifier();
64     }
65 }
66 */
67
68 // Connects to Arduino via serial port
69 foreach(const QSerialPortInfo &serialPortInfo, QSerialPortInfo::
    availablePorts()){
70     if(serialPortInfo.hasVendorIdentifier() && serialPortInfo.
        hasProductIdentifier()){
71         if(serialPortInfo.vendorIdentifier() ==
            arduino_due_vendor_id){
72             if(serialPortInfo.productIdentifier() ==
                arduino_due_product_id){
73                 arduino_port_name = serialPortInfo.portName();
74                 arduino_is_available = true;
75             }
76         }
77     }
78 }
79
80 if(arduino_is_available){
81     // Open and configure the serialport
82     arduino->setPortName(arduino_port_name);
83     arduino->open(QSerialPort::ReadWrite);
84     arduino->setBaudRate(QSerialPort::Baud9600);
85     arduino->setDataBits(QSerialPort::Data8);
86     arduino->setParity(QSerialPort::NoParity);
87     arduino->setStopBits(QSerialPort::OneStop);
88     arduino->setFlowControl(QSerialPort::NoFlowControl);
89     QObject::connect(arduino, SIGNAL(readyRead()), this, SLOT(
        readSerial()));
90     qDebug() << "Connected to Arduino!";
91 }
92 else{
93     // Give error message if not available
94     QMessageBox::warning(this, "Port error", "Couldn't find the
        Arduino!");
95 }
96 }
97
98 Dialog::~Dialog()
99 {
100     if(arduino->isOpen()){
101         arduino->close();
102     }
103     delete ui;
104 }

```

```

105
106 void Dialog::updateArduino(QString command)
107 {
108     if(arduino->isWritable()){
109         arduino->write(command.toStdString().c_str());
110     }else{
111         qDebug() << "Couldn't write to serial!";
112     }
113 }
114
115 void Dialog::readSerial()
116 {
117     QStringList buffer_split = serialBuffer.split(";");
118
119     if (buffer_split.length() < 3) {
120         serialData = arduino->readAll();
121         serialBuffer = serialBuffer + QString::fromStdString(
            serialData.toStdString());
122         serialData.clear();
123     }
124     else{
125         serialBuffer = "";
126         parsed_data = buffer_split[1];
127         // qDebug() << parsed_data << "\n";
128
129         // If the parsed data has a $ sign at index 0, then recognize
            it as a callback command
130         if (parsed_data.at(0) == '$') {
131             parseCallbackCommands(parsed_data);
132         }
133         else {
134             // qDebug() << parsed_data << "\n";
135         }
136     }
137 }
138
139
140 void Dialog::updatePlot()
141 {
142     xData.prepend(transferFunctionInput);
143     yData.prepend(transferFunctionOutput);
144
145     while (xData.size() > 1000) {
146         xData.removeLast();
147         yData.removeLast();
148     }
149
150     QCustomPlot *plot = ui->transferFunctionPlot;
151     plot->graph(0)->setData(xData, yData);
152     plot->replot();
153 }
154
155
156 void Dialog::parseCallbackCommands(QString command)
157 {

```

```

158 QString processedCommand = command.mid(1);
159 qDebug() << "Processed_command:" << processedCommand;
160
161 // Only update GUI if processed command has 9 elements
162 QStringList processedCommand_split = processedCommand.split(",");
163 // qDebug() << "Command length: " << processedCommand_split.
    length();
164
165 if (processedCommand_split.length() == 9) {
166
167     // Motor states
168     QString servoMotorState = processedCommand_split.at(0);
169     QString stepperMotorState = processedCommand_split.at(1);
170     QString velDCMotorState = processedCommand_split.at(2);
171     QString angleDCMotorState = processedCommand_split.at(3);
172
173     ui->servo_angle_state->display(servoMotorState);
174     ui->stepper_angle_state->display(stepperMotorState);
175     ui->dc_rpm_state->display(velDCMotorState);
176     ui->dc_angle_state->display(angleDCMotorState);
177
178     // Sensor states
179     QString potentiometerSensorState = processedCommand_split.at
        (4);
180     QString imuSensorState = processedCommand_split.at(5);
181     QString temperatureSensorState = processedCommand_split.at(6)
        ;
182     QString ultrasonicSensorState = processedCommand_split.at(7);
183
184     // Filtering for ultrasonic sensor
185     int ultrasonicReading = ultrasonicSensorState.toInt();
186     if (ultrasonicReadings.size() >= 5) {
187         ultrasonicReadings.erase(ultrasonicReadings.begin());
188     }
189     ultrasonicReadings.push_back(ultrasonicReading);
190     int filteredUltrasonicValue = filterMean(ultrasonicReadings);
191
192     ui->potentiometer_sensor_state->display(
        potentiometerSensorState);
193     ui->IMU_sensor_state->display(imuSensorState);
194     ui->temperature_sensor_state->display(temperatureSensorState)
        ;
195     ui->ultrasonic_sensor_state->display(filteredUltrasonicValue)
        ;
196     // ui->ultrasonic_sensor_state->display(ultrasonicSensorState
        );
197
198     // Transfer function
199     QString transferFunctionState = processedCommand_split.at(8);
200     QStringList transferFunctionState_split =
        transferFunctionState.split(":");
201
202     QString transferFunctionInputString =
        transferFunctionState_split.at(0);

```

```

203         QString transferFunctionOutputString =
                transferFunctionState_split.at(1);
204
205         transferFunctionInput = transferFunctionInputString.toDouble
                ();
206         transferFunctionOutput = transferFunctionOutputString.
                toDouble();
207     }
208 }
209
210
211 void Dialog::on_servo_slider_valueChanged(int value)
212 {
213     QString command = QString("R%1;").arg(value);
214     qDebug() << "Slider_value:" << value << "Command:" << command;
215     updateArduino(command);
216 }
217
218
219 void Dialog::on_stepper_slider_valueChanged(int value)
220 {
221     QString command = QString("S%1;").arg(value);
222     qDebug() << "Slider_value:" << value << "Command:" << command;
223     updateArduino(command);
224 }
225
226 void Dialog::on_stepper_mode_button_toggled(bool checked)
227 {
228     QString command = QString("B%1;").arg(checked);
229     qDebug() << "Button_value:" << checked << "Command:" << command;
230     updateArduino(command);
231 }
232
233 void Dialog::onDCVelCommentSubmitted()
234 {
235     QString comment = ui->dc_vel_textbox->text();
236
237     QString command = QString("V%1;").arg(comment);
238     qDebug() << "Text_box_value:" << comment << "Command:" << command
                ;
239     updateArduino(command);
240
241     ui->dc_vel_textbox->clear();
242 }
243
244 void Dialog::onDCPosCommentSubmitted()
245 {
246     QString comment = ui->dc_angle_textbox->text();
247
248     QString command = QString("A%1;").arg(comment);
249     qDebug() << "Text_box_value:" << comment << "Command:" << command
                ;
250     updateArduino(command);
251
252     ui->dc_angle_textbox->clear();

```

```

253 }
254
255 int Dialog::filterMean(std::vector<int>& arr) {
256     if(arr.empty()) {
257         return 0;
258     }
259
260     int sum = 0;
261
262     for (size_t i = 1; i < arr.size(); i++) {
263         sum += arr[i];
264     }
265
266     return sum / arr.size();
267 }

```

Listing 3: dialog.cpp

```

1  <?xml version="1.0" encoding="UTF-8"?>
2  <ui version="4.0">
3      <class>Dialog</class>
4      <widget class="QDialog" name="Dialog">
5          <property name="geometry">
6              <rect>
7                  <x>0</x>
8                  <y>0</y>
9                  <width>1280</width>
10                 <height>1024</height>
11             </rect>
12         </property>
13         <property name="windowTitle">
14             <string>Dialog</string>
15         </property>
16         <property name="autoFillBackground">
17             <bool>false</bool>
18         </property>
19         <widget class="QGroupBox" name="groupBox">
20             <property name="geometry">
21                 <rect>
22                     <x>10</x>
23                     <y>20</y>
24                     <width>641</width>
25                     <height>471</height>
26                 </rect>
27             </property>
28             <property name="font">
29                 <font>
30                     <pointsize>13</pointsize>
31                 </font>
32             </property>
33             <property name="title">
34                 <string>Motor Control</string>
35             </property>
36             <property name="alignment">
37                 <set>Qt::AlignmentFlag::AlignCenter</set>
38             </property>

```

```

39 <widget class="QGroupBox" name="groupBox_2">
40 <property name="geometry">
41 <rect>
42 <x>10</x>
43 <y>40</y>
44 <width>421</width>
45 <height>91</height>
46 </rect>
47 </property>
48 <property name="title">
49 <string>RC Servo Motor</string>
50 </property>
51 <property name="alignment">
52 <set>Qt::AlignmentFlag::AlignLeading|Qt::AlignmentFlag::
    AlignLeft|Qt::AlignmentFlag::AlignVCenter</set>
53 </property>
54 <layout class="QHBoxLayout" name="horizontalLayout">
55 <item>
56 <widget class="QLabel" name="label">
57 <property name="text">
58 <string>Angle (degrees)</string>
59 </property>
60 </widget>
61 </item>
62 <item>
63 <widget class="QSlider" name="servo_slider">
64 <property name="minimum">
65 <number>0</number>
66 </property>
67 <property name="maximum">
68 <number>180</number>
69 </property>
70 <property name="orientation">
71 <enum>Qt::Orientation::Horizontal</enum>
72 </property>
73 </widget>
74 </item>
75 </layout>
76 </widget>
77 <widget class="QGroupBox" name="groupBox_4">
78 <property name="geometry">
79 <rect>
80 <x>440</x>
81 <y>40</y>
82 <width>191</width>
83 <height>91</height>
84 </rect>
85 </property>
86 <property name="title">
87 <string>RC Servo Motor Angle</string>
88 </property>
89 <property name="alignment">
90 <set>Qt::AlignmentFlag::AlignCenter</set>
91 </property>
92 <layout class="QHBoxLayout" name="horizontalLayout_3">

```

```

93     <item>
94         <widget class="QLCDNumber" name="servo_angle_state">
95             <property name="intValue" stdset="0">
96                 <number>0</number>
97             </property>
98         </widget>
99     </item>
100 </layout>
101 </widget>
102 <widget class="QGroupBox" name="groupBox_5">
103     <property name="geometry">
104         <rect>
105             <x>440</x>
106             <y>140</y>
107             <width>191</width>
108             <height>91</height>
109         </rect>
110     </property>
111     <property name="title">
112         <string>Stepper Motor Angle</string>
113     </property>
114     <property name="alignment">
115         <set>Qt::AlignmentFlag::AlignCenter</set>
116     </property>
117     <layout class="QHBoxLayout" name="horizontalLayout_4">
118         <item>
119             <widget class="QLCDNumber" name="stepper_angle_state"/>
120         </item>
121     </layout>
122 </widget>
123 <widget class="QGroupBox" name="groupBox_6">
124     <property name="geometry">
125         <rect>
126             <x>10</x>
127             <y>280</y>
128             <width>421</width>
129             <height>181</height>
130         </rect>
131     </property>
132     <property name="title">
133         <string>DC Motor</string>
134     </property>
135     <property name="alignment">
136         <set>Qt::AlignmentFlag::AlignLeading|Qt::AlignmentFlag::
            AlignLeft|Qt::AlignmentFlag::AlignVCenter</set>
137     </property>
138     <layout class="QVBoxLayout" name="verticalLayout">
139         <item>
140             <layout class="QHBoxLayout" name="horizontalLayout_10">
141                 <item>
142                     <widget class="QLabel" name="label_3">
143                         <property name="text">
144                             <string>Velocity (RPM)</string>
145                         </property>
146                     </widget>

```

```

147     </item>
148     <item>
149         <widget class="QLineEdit" name="dc_vel_textbox"/>
150     </item>
151 </layout>
152 </item>
153 <item>
154     <layout class="QHBoxLayout" name="horizontalLayout_11">
155         <item>
156             <widget class="QLabel" name="label_4">
157                 <property name="text">
158                     <string>Position (degrees)</string>
159                 </property>
160             </widget>
161         </item>
162         <item>
163             <widget class="QLineEdit" name="dc_angle_textbox"/>
164         </item>
165     </layout>
166 </item>
167 </layout>
168 </widget>
169 <widget class="QGroupBox" name="groupBox_7">
170     <property name="geometry">
171         <rect>
172             <x>440</x>
173             <y>250</y>
174             <width>191</width>
175             <height>91</height>
176         </rect>
177     </property>
178     <property name="title">
179         <string>DC Motor RPM</string>
180     </property>
181     <property name="alignment">
182         <set>Qt::AlignmentFlag::AlignCenter</set>
183     </property>
184     <layout class="QHBoxLayout" name="horizontalLayout_12">
185         <item>
186             <widget class="QLCDNumber" name="dc_rpm_state"/>
187         </item>
188     </layout>
189 </widget>
190 <widget class="QGroupBox" name="groupBox_13">
191     <property name="geometry">
192         <rect>
193             <x>440</x>
194             <y>350</y>
195             <width>191</width>
196             <height>91</height>
197         </rect>
198     </property>
199     <property name="title">
200         <string>DC Motor Angle</string>
201     </property>

```

```

202 <property name="alignment">
203 <set>Qt::AlignmentFlag::AlignCenter</set>
204 </property>
205 <layout class="QHBoxLayout" name="horizontalLayout_13">
206 <item>
207 <widget class="QLCDNumber" name="dc_angle_state"/>
208 </item>
209 </layout>
210 </widget>
211 <widget class="QGroupBox" name="groupBox_12">
212 <property name="geometry">
213 <rect>
214 <x>10</x>
215 <y>140</y>
216 <width>421</width>
217 <height>131</height>
218 </rect>
219 </property>
220 <property name="title">
221 <string>Stepper Motor</string>
222 </property>
223 <property name="alignment">
224 <set>Qt::AlignmentFlag::AlignLeading|Qt::AlignmentFlag::
    AlignLeft|Qt::AlignmentFlag::AlignVCenter</set>
225 </property>
226 <layout class="QVBoxLayout" name="verticalLayout_2">
227 <item alignment="Qt::AlignmentFlag::AlignHCenter">
228 <widget class="QRadioButton" name="stepper_mode_button">
229 <property name="text">
230 <string>Switch Mode</string>
231 </property>
232 </widget>
233 </item>
234 <item>
235 <layout class="QHBoxLayout" name="horizontalLayout_16">
236 <item>
237 <widget class="QLabel" name="label_2">
238 <property name="text">
239 <string>Angle (degrees)</string>
240 </property>
241 </widget>
242 </item>
243 <item>
244 <widget class="QSlider" name="stepper_slider">
245 <property name="tabletTracking">
246 <bool>>false</bool>
247 </property>
248 <property name="acceptDrops">
249 <bool>>false</bool>
250 </property>
251 <property name="autoFillBackground">
252 <bool>>false</bool>
253 </property>
254 <property name="minimum">
255 <number>-180</number>

```

```

256         </property>
257         <property name="maximum">
258             <number>180</number>
259         </property>
260         <property name="value">
261             <number>0</number>
262         </property>
263         <property name="sliderPosition">
264             <number>0</number>
265         </property>
266         <property name="orientation">
267             <enum>Qt::Orientation::Horizontal</enum>
268         </property>
269     </widget>
270 </item>
271 </layout>
272 </item>
273 </layout>
274 </widget>
275 </widget>
276 <widget class="QGroupBox" name="groupBox_14">
277     <property name="geometry">
278         <rect>
279             <x>670</x>
280             <y>20</y>
281             <width>241</width>
282             <height>471</height>
283         </rect>
284     </property>
285     <property name="font">
286         <font>
287             <pointsize>13</pointsize>
288         </font>
289     </property>
290     <property name="title">
291         <string>Sensor Readings</string>
292     </property>
293     <property name="alignment">
294         <set>Qt::AlignmentFlag::AlignCenter</set>
295     </property>
296     <layout class="QVBoxLayout" name="verticalLayout_3">
297         <item>
298             <widget class="QGroupBox" name="groupBox_10">
299                 <property name="title">
300                     <string>Potentiometer Sensor</string>
301                 </property>
302                 <property name="alignment">
303                     <set>Qt::AlignmentFlag::AlignCenter</set>
304                 </property>
305                 <layout class="QHBoxLayout" name="horizontalLayout_7">
306                     <item>
307                         <widget class="QLCDNumber" name="potentiometer_sensor_state">
308                             <property name="intValue" stdset="0">
309                                 <number>0</number>
310                             </property>

```

```

311     </widget>
312 </item>
313 </layout>
314 </widget>
315 </item>
316 <item>
317 <widget class="QGroupBox" name="groupBox_11">
318 <property name="title">
319 <string>IMU Sensor Pitch Angle</string>
320 </property>
321 <property name="alignment">
322 <set>Qt::AlignmentFlag::AlignCenter</set>
323 </property>
324 <layout class="QHBoxLayout" name="horizontalLayout_8">
325 <item>
326 <widget class="QLCDNumber" name="IMU_sensor_state">
327 <property name="intValue" stdset="0">
328 <number>0</number>
329 </property>
330 </widget>
331 </item>
332 </layout>
333 </widget>
334 </item>
335 <item>
336 <widget class="QGroupBox" name="groupBox_8">
337 <property name="title">
338 <string>Temperature (Celcius)</string>
339 </property>
340 <property name="alignment">
341 <set>Qt::AlignmentFlag::AlignCenter</set>
342 </property>
343 <layout class="QHBoxLayout" name="horizontalLayout_5">
344 <item>
345 <widget class="QLCDNumber" name="temperature_sensor_state">
346 <property name="intValue" stdset="0">
347 <number>0</number>
348 </property>
349 </widget>
350 </item>
351 </layout>
352 </widget>
353 </item>
354 <item>
355 <widget class="QGroupBox" name="groupBox_9">
356 <property name="title">
357 <string>Ultrasonic Sensor (cm)</string>
358 </property>
359 <property name="alignment">
360 <set>Qt::AlignmentFlag::AlignCenter</set>
361 </property>
362 <layout class="QHBoxLayout" name="horizontalLayout_6">
363 <item>
364 <widget class="QLCDNumber" name="ultrasonic_sensor_state"/>
365 </item>

```

```

366     </layout>
367 </widget>
368 </item>
369 </layout>
370 </widget>
371 <widget class="QGroupBox" name="groupBox_22">
372 <property name="geometry">
373 <rect>
374 <x>10</x>
375 <y>500</y>
376 <width>901</width>
377 <height>311</height>
378 </rect>
379 </property>
380 <property name="font">
381 <font>
382 <pointsize>13</pointsize>
383 </font>
384 </property>
385 <property name="title">
386 <string>Transfer Function</string>
387 </property>
388 <property name="alignment">
389 <set>Qt::AlignmentFlag::AlignCenter</set>
390 </property>
391 <layout class="QVBoxLayout" name="verticalLayout_4">
392 <item>
393 <widget class="QCustomPlot" name="transferFunctionPlot" native="
    true"/>
394 </item>
395 </layout>
396 </widget>
397 </widget>
398 <customwidgets>
399 <customwidget>
400 <class>QCustomPlot</class>
401 <extends>QWidget</extends>
402 <header>qcustomplot.h</header>
403 <container>1</container>
404 </customwidget>
405 </customwidgets>
406 <resources/>
407 <connections/>
408 </ui>

```

Listing 4: dialog.ui

5.2 Arduino

I was responsible for coding the skeleton template of the Arduino code. My teammates were responsible for implementing their respective controllers and callbacks after each // TODO: IMPLEMENT FUNCTION BELOW comment.

```

1 #include <Adafruit_Sensor.h>
2 #include <Adafruit_MPU6050.h>

```

```

3  #include <Wire.h>
4  #include <Servo.h>
5  #include <SharpIR.h>
6  #include <RoboClaw.h>
7  #include <AccelStepper.h>
8
9  #define SERIAL_PORT Serial
10
11 #define ADDRESS 0x80
12
13 // Motor & Encoder parameters
14 #define ENCODER_TICKS_PER_REV 3416
15 #define DEGREE_TO_TICKS (ENCODER_TICKS_PER_REV / 360.0)
16
17 // Position PID Tuning
18 #define Kp_pos 2.0
19 #define Ki_pos 0.5
20 #define Kd_pos 1.0
21
22 // Velocity PID Tuning
23 #define Kp_vel 1.0
24 #define Ki_vel 0.5
25 #define Kd_vel 0.25
26
27 // Maximum speed in encoder counts per second
28 #define MAX_QPPS 6718
29
30 // Pins
31 #define EN_StepperDriver 2
32 #define Stp_StepperDriver 3
33 #define Dir_StepperDriver 4
34 #define servoPin 6
35 #define PushButtonPin 7
36 #define PotentiometerPin A0
37 #define temperaturePin A1
38 #define ultrasonicPin A2
39 #define PushbuttonPin 7
40
41 AccelStepper stepper(AccelStepper::DRIVER, Stp_StepperDriver,
42                      Dir_StepperDriver);
43
44 // GLOBAL VARIABLES
45 // Note: GUI will execute commands sent by Arduino once every 2
46 // intervals as it discards every other command due to serial buffer
47 unsigned long previousMillis = 0;
48 const unsigned long interval = 100;
49
50 Adafruit_MPU6050 mpu;
51 Servo servo;
52 RoboClaw roboclaw(&Serial1, 10000);
53
54 int servoAngle = 0;
55 int dc_motor_speed = 0;
56 int dc_motor_angle = 0;

```

```

56 double cm = 0.0;
57
58 int PotControlFlag = 0;
59 volatile int PotVal = 0;
60 volatile int globalStepperValue = 0;
61 volatile int globalStepperAngle = 0;
62
63 // Debounce variables
64 volatile unsigned long lastDebounceTime = 0;
65 const unsigned long debounceDelay = 100;
66 const int incrementServo = 30;
67
68 bool isMoving = false;
69 uint32_t targetPosition = 0;
70
71 void setup() {
72     SERIAL_PORT.begin(9600);
73     Serial1.begin(38400);
74     while (!SERIAL_PORT) {
75         // Wait for the serial port to be ready
76     }
77
78     // IMU
79     if (!mpu.begin()) {
80         Serial.println("Failed to find MPU6050 chip");
81         while (1)
82             ;
83     }
84
85     // Servo Motor
86     servo.attach(servoPin);
87     servo.write(0);
88
89     // Push Button
90     attachInterrupt(digitalPinToInterrupt(PushbuttonPin), pushISR,
91                     FALLING);
92
93     // DC Motor
94     unsigned long startTime = millis();
95
96     // Stepper
97     pinMode(EN_StepperDriver, OUTPUT);
98     digitalWrite(EN_StepperDriver, LOW); // enable stepper(s)
99     stepper.setMaxSpeed(2000);
100    stepper.setAcceleration(1000);
101    stepper.setSpeed(0);
102
103    // // Initialize RoboClaw
104    // if (!roboclaw.ReadError(ADDRESS)) {
105    //     Serial.println("RoboClaw connected successfully.");
106    // } else {
107    //     Serial.println("Error detected in RoboClaw!");
108    // }
109
110    roboclaw.SetM1VelocityPID(ADDRESS, Kp_vel, Ki_vel, Kd_vel, MAX_QPPS

```

```

    );
110  roboclaw.SetM1PositionPID(ADDRESS, Kp_pos, Ki_pos, Kd_pos, Kp_vel,
    Ki_vel, Kd_vel, MAX_QPPS);
111
112  roboclaw.SpeedM1(ADDRESS, 0);
113  // Serial.println("Motor stopped at startup.");
114
115  SERIAL_PORT.print("Arduino_Due_Serial_is_ready!");
116 }
117
118
119 void loop() {
120   if (isMoving) {
121     uint32_t currentPos = roboclaw.ReadEncM1(ADDRESS);
122     if (abs((int32_t)(currentPos - targetPosition)) <= 15) { //
        Position tolerance
123     roboclaw.SpeedM1(ADDRESS, 0); // Stop
        motor
124     // Serial.println("Target position reached.");
125     isMoving = false; // Reset movement flag
126   }
127 }
128
129 // Check if data is available to read from the serial port
130 if (SERIAL_PORT.available() > 0) {
131   // Read the incoming string
132   String receivedString = SERIAL_PORT.readStringUntil(';');
133
134   // // Echo the string back to the serial port
135   // SERIAL_PORT.print("Arduino received command: ");
136   // SERIAL_PORT.print(receivedString);
137   // SERIAL_PORT.print(";");
138   // SERIAL_PORT.flush();
139
140   if (receivedString.length() > 1) {
141     char commandType = receivedString.charAt(0);
142
143     String valueString = receivedString.substring(1);
144     if (isNumeric(valueString)) {
145       int commandValue = valueString.toInt();
146       handleCommand(commandType, commandValue);
147     }
148   }
149 }
150
151 unsigned long currentMillis = millis();
152 if (currentMillis - previousMillis >= interval) {
153   previousMillis = currentMillis;
154   timerCallback();
155 }
156
157 stepperCallback();
158 }
159
160 void timerCallback() {

```

```

161 // SERIAL_PORT.print("Timer callback executed at: ");
162 // SERIAL_PORT.print(previousMillis);
163 // SERIAL_PORT.print(";");
164
165 // A "$" is used to indicate the serial port return is a command
166 String serialReturn;
167 serialReturn.concat("$");
168
169 int servoMotorState = servoMotorStateCallback();
170 serialReturn.concat(servoMotorState);
171 serialReturn.concat(",");
172
173 int stepperMotorState = stepperMotorStateCallback();
174 serialReturn.concat(stepperMotorState);
175 serialReturn.concat(",");
176
177 int velDCMotorState = velDCMotorStateCallback();
178 serialReturn.concat(velDCMotorState);
179 serialReturn.concat(",");
180
181 int angledDCMotorState = angledDCMotorStateCallback();
182 serialReturn.concat(angledDCMotorState);
183 serialReturn.concat(",");
184
185 int potentiometerSensorState = potentiometerSensorCallback();
186 serialReturn.concat(potentiometerSensorState);
187 serialReturn.concat(",");
188
189 double imuSensorState = imuSensorCallback();
190 serialReturn.concat(imuSensorState);
191 serialReturn.concat(",");
192
193 double temperatureSensorState = temperatureSensorCallback();
194 serialReturn.concat(temperatureSensorState);
195 serialReturn.concat(",");
196
197 int ultrasonicSensorState = ultrasonicSensorCallback();
198 serialReturn.concat(ultrasonicSensorState);
199 serialReturn.concat(",");
200
201 double electricalInput = analogRead(ultrasonicPin);
202 double transferFunctionState = transferFunctionCallback(
    electricalInput);
203 double electricalVoltage = analogRead(ultrasonicPin) * (5.0 /
    1023.0);
204
205 serialReturn.concat(electricalVoltage);
206 serialReturn.concat(":");
207 serialReturn.concat(transferFunctionState);
208
209 SERIAL_PORT.print(serialReturn);
210 SERIAL_PORT.print(";");
211 }
212
213

```

```

214 void handleCommand(char commandType, int value) {
215     switch (commandType) {
216         case 'R':
217             servoMotorController(value);
218             break;
219         case 'S':
220             stepperMotorController(value);
221             break;
222         case 'V':
223             velDCMotorController(value);
224             break;
225         case 'A':
226             angleDCMotorController(value);
227             break;
228         case 'B':
229             buttonStepperMotorController(value);
230             break;
231         default:
232             break;
233     }
234 }
235
236
237 bool isNumeric(String str) {
238     if (str.length() == 0) return false;
239
240     int startIndex = 0;
241
242     if (str[0] == '-') {
243         if (str.length() == 1) return false;
244         startIndex = 1;
245     }
246
247     for (unsigned int i = startIndex; i < str.length(); i++) {
248         if (!isDigit(str[i])) {
249             return false;
250         }
251     }
252
253     return true;
254 }
255
256
257 // CONTROLLER FUNCTIONS
258
259 void servoMotorController(int control) {
260     /*
261     INPUT: Integer in min/max range of 0 to 180 corresponding to
           desired angle
262     OUTPUT: Void
263     */
264
265     SERIAL_PORT.print("Servo_motor_controller_received_command:");
266     SERIAL_PORT.print(control);
267     SERIAL_PORT.print(";");

```

```

268
269 // TODO: IMPLEMENT FUNCTION BELOW
270 servoAngle = control;
271 servo.write(servoAngle);
272 }
273
274 void stepperMotorController(int control) {
275     /*
276     INPUT: Integer in min/max range of -180 to 180 corresponding to
           desired angle
277     OUTPUT: Void
278     */
279
280     SERIAL_PORT.print("Stepper_motor_controller_received_command:");
281     SERIAL_PORT.print(control);
282     SERIAL_PORT.print(";");
283
284     // TODO: IMPLEMENT FUNCTION BELOW
285     if (PotControlFlag == 0) {
286         globalStepperValue = map(control, -180, 180, -1600, 1600);
287         globalStepperAngle = control;
288     }
289 }
290
291 void velDCMotorController(int control) {
292     /*
293     INPUT: Integer in min/max range of 0 to 118 corresponding to
           desired RPM
294     OUTPUT: Void
295     */
296
297     SERIAL_PORT.print("Velocity_DC_motor_controller_received_command:");
298     SERIAL_PORT.print(control);
299     SERIAL_PORT.print(";");
300
301     // TODO: IMPLEMENT FUNCTION BELOW
302     // Set motor velocity (positive for forward, negative for reverse)
303     int dc_motor_speed = (control / 118.0) * 100.0;
304     int encoderSpeed = (dc_motor_speed * MAX_QPPS) / 100; // Scale
           input speed (user enters 0-100%)
305     roboclaw.SpeedM1(ADDRESS, encoderSpeed);
306 }
307
308 void angleDCMotorController(int control) {
309     /*
310     INPUT: Integer in min/max range of 0 to 360 corresponding to
           desired angle
311     OUTPUT: Void
312     */
313
314     // SERIAL_PORT.print("Angle DC motor controller received command:");
315     // SERIAL_PORT.print(control);
316     // SERIAL_PORT.print(";");

```

```

317
318 // TODO: IMPLEMENT FUNCTION BELOW
319 uint32_t currentPos = roboclaw.ReadEncM1(ADDRESS);
320 targetPosition = currentPos + (control * DEGREE_TO_TICKS);
321
322 // Serial.print("Moving motor to position: ");
323 // Serial.println(targetPosition);
324
325 roboclaw.SpeedAccelDeccelPositionM1(ADDRESS, 10000, MAX_QPPS,
    10000, targetPosition, 0);
326
327 isMoving = true; // Set flag for movement tracking
328 }
329
330 void buttonStepperMotorController(int control) {
331     /*
332     INPUT: Boolean with 1 indicating GUI control and 1 indicating
    potentiometer control
333     OUTPUT: Void
334     */
335
336     SERIAL_PORT.print("Button_controller_received_command:");
337     SERIAL_PORT.print(control);
338     SERIAL_PORT.print(";");
339
340     // TODO: IMPLEMENT FUNCTION BELOW
341     PotControlFlag = control;
342 }
343
344
345 // CALLBACK FUNCTIONS
346 int servoMotorStateCallback() {
347     /*
348     INPUT: Void
349     OUTPUT: Integer in min/max range of 0 to 180 corresponding to servo
    motor angle
350     */
351
352     // TODO: IMPLEMENT FUNCTION BELOW
353     return servoAngle;
354 }
355
356 int stepperMotorStateCallback() {
357     /*
358     INPUT: Void
359     OUTPUT: Integer in min/max range of -180 to 180 corresponding to
    stepper motor angle
360     */
361
362     // TODO: IMPLEMENT FUNCTION BELOW
363
364     return globalStepperAngle;
365 }
366
367 int velDCMotorStateCallback() {

```

```

368  /*
369  INPUT: Void
370  OUTPUT: Integer in min/max range of -118 to 118 corresponding to DC
        motor RPM
371  */
372
373  // TODO: IMPLEMENT FUNCTION BELOW
374
375  int speed = roboclaw.ReadSpeedM1(ADDRESS);
376  speed = speed * 118 / 6718;
377
378  return speed;
379 }
380
381 int angleDCMotorStateCallback() {
382  /*
383  INPUT: Void
384  OUTPUT: Integer in min/max range of -360 to 360 corresponding to DC
        motor angle
385  */
386
387  // TODO: IMPLEMENT FUNCTION BELOW
388
389  int enc = roboclaw.ReadEncM1(ADDRESS);
390  int angle = (enc * 360) / 3416;
391  angle = angle % 360;
392
393  return angle;
394 }
395
396 int potentiometerSensorCallback() {
397  /*
398  INPUT: Void
399  OUTPUT: Integer corresponding to potentiometer reading
400  */
401
402  // TODO: IMPLEMENT FUNCTION BELOW
403  PotVal = analogRead(PotentiometerPin);
404
405  if (PotControlFlag == 1) {
406      globalStepperValue = map(PotVal, 0, 1022, -1600, 1600);
407      globalStepperAngle = map(globalStepperValue, -1600, 1600, -180,
        180);
408  }
409
410  return PotVal;
411 }
412
413 double imuSensorCallback() {
414  /*
415  INPUT: Void
416  OUTPUT: Double corresponding to sensed IMU pitch reading
417  */
418
419  // TODO: IMPLEMENT FUNCTION BELOW

```

```

420     sensors_event_t a, g, temp;
421     mpu.getEvent(&a, &g, &temp);
422
423     // Pitch using accel data
424     double pitchAccel = atan2(a.acceleration.x, a.acceleration.z) * 180
        / PI;
425
426     return pitchAccel;
427 }
428
429 double temperatureSensorCallback() {
430     /*
431     INPUT: Void
432     OUTPUT: Double corresponding to Temperature reading (degree celsius
        )
433     */
434
435     // TODO: IMPLEMENT FUNCTION BELOW
436     int reading = analogRead(temperaturePin);
437     double voltage = reading * 3.3;
438     voltage /= 1024.0;
439
440     double temperatureC = (voltage - 1.0) * 100;
441
442     return temperatureC;
443 }
444
445 int ultrasonicSensorCallback() {
446     /*
447     INPUT: Void
448     OUTPUT: Integer corresponding to ultrasonic reading (cm)
449     */
450
451     // TODO: IMPLEMENT FUNCTION BELOW
452     cm = analogRead(ultrasonicPin);
453     cm = transferFunctionCallback(cm);
454
455     return int(cm);
456 }
457
458 // OTHER FUNCTIONS
459 void pushISR() {
460     /*
461     INPUT: Void
462     OUTPUT: Void
463     */
464
465     // TODO: IMPLEMENT FUNCTION BELOW
466     unsigned long currentTime = millis();
467     if ((currentTime - lastDebounceTime) > debounceDelay) {
468         servoAngle += incrementServo;
469         if (servoAngle > 180) {
470             servoAngle = 0;
471         }
472         lastDebounceTime = currentTime;

```

```

473     servo.write(servoAngle);
474 }
475 }
476
477 double transferFunctionCallback(double electricalInput) {
478     /*
479     INPUT: Double corresponding to electrical input voltage
480     OUTPUT: Double corresponding to ultrasonic reading (cm)
481     */
482
483     // TODO: IMPLEMENT FUNCTION BELOW
484     double val = electricalInput * 0.498 * 2.54;
485
486     return val;
487 }
488
489 void stepperCallback() {
490     /*
491     INPUT: Void
492     OUTPUT: Void
493     */
494
495     // TODO: IMPLEMENT FUNCTION BELOW
496     stepper.moveTo(globalStepperValue);
497     stepper.run();
498 }

```

Listing 5: arduino_gui.ino

6 Sensors and Motor Control Lab Quiz

6.1 Q1: ADXL335 Accelerometer

6.1.1 What is the sensor's range?

The minimum range of the sensor is $[-3g, 3g]$ (although it has a typical range of $[-3.6g, 3.6g]$), where g is the gravity constant.

6.1.2 What is the sensor's dynamic range?

The typical dynamic range is $7.2g$, the minimum dynamic range is $6g$.

6.1.3 What is the purpose of the capacitor C_{DC} on the LHS of the functional block diagram on p. 1? How does it achieve this?

From the block diagram, the C_{DC} capacitor is placed at the ends of the power supply. This means that it is used to regulate the voltage of the power input and filter out any high frequency noise in the voltage that may cause erroneous sensor readings. The capacitor can do this as it opposes sudden changes in voltage. This is because it can act as a current source/sink to counterbalance sudden decreases/increases in voltage.

6.1.4 Write an equation for the sensor's transfer function.

$$V_{out} = 1.5V + (0.3V/g) \times a$$

Where a is acceleration, g is the gravity constant, and V is volts.

6.1.5 What is the largest expected nonlinearity error in g?

The largest expected nonlinearity error is $\pm 0.3\%$ of $7.2g$, which turns out to be $\pm 0.0216g$ (i.e. ± 0.0216 in g).

6.1.6 What is the sensor's bandwidth for the X- and Y-axes?

The bandwidth is 1600 Hz.

6.1.7 How much noise do you expect in the X- and Y-axis sensor signals when your measurement bandwidth is 25 Hz?

The noise density is given as $150 \mu g / \sqrt{Hz}$. So at 25 Hz, the noise is $150 \times \sqrt{25 \times 1.6} = 948.68 \mu g$ (the 1.6 multiplier is the filter constant given on p. 11). Note that μg refers to gravity, and not grams.

6.1.8 If you didn't have the datasheet, how would you determine the RMS noise experimentally? State any assumptions and list the steps you would take.

The following steps could be taken:

1. Take several measurements experimentally.
2. Calculate the error (by subtracting the mean).
3. Take the square of the errors.

4. Calculate the mean.
5. Take the square root.

Some assumptions are:

- The noise source is stationary.
- The sensor is not being disturbed by anything other than the white noise.
- The measurement bandwidth is well-defined.
- The sensor is calibrated.

6.2 Q2: Signal Conditioning

6.2.1 Filtering: Name at least two problems you might have in using a moving average filter.

- A moving average filter lags behind the signal as it averages over several past data points, creating delays in real-time responsiveness.
- A moving average filter is not able to distinguish closely spaced frequencies as it averages over the data points. This may create problems as important signals could be lost.

6.2.2 Filtering: Name at least two problems you might have in using a median filter.

- A median filter is relatively expensive to compute as it requires sorting and storing previous values.
- A median filter is not able to effectively filter out continuously distributed noise such as Gaussian noise. This is because Gaussian noise introduces small fluctuations about the true value. Taking the median value in a window leaves much of the Gaussian noise intact as the filter is more effective at filtering out impulse noise.

6.2.3 Opamps: In the following questions, you want to calibrate a linear sensor using the circuit in Fig. 1 so that its output range is 0 to 5V. Identify in each case: 1) which of V1 and V2 will be the input voltage and which the reference voltage; 2) the values of the ratio R_f/R_i and the reference voltage. If the calibration can't be done with this circuit, explain why.

Referring to the Circuits lecture (Jan 16) Slide 75, the basic op-amp equation is given by:

$$V_{out} = (V_2 - V_1) \frac{R_f}{R_i} + V_2$$

When setting one voltage as reference and the other as input, the equation becomes:

$$\begin{array}{l}
 \text{Gain} \qquad \text{Offset} \\
 \text{V}_1 (V_{ref}) \text{ reference, V}_2 (V_{in}) \text{ varies: } V_{out} = V_{in} \left(1 + \frac{R_f}{R_i} \right) - V_{ref} \left(\frac{R_f}{R_i} \right) \\
 \text{V}_2 (V_{ref}) \text{ reference, V}_1 (V_{in}) \text{ varies: } V_{out} = -V_{in} \left(\frac{R_f}{R_i} \right) + V_{ref} \left(1 + \frac{R_f}{R_i} \right)
 \end{array}$$

6.2.4 Your uncalibrated sensor has a range of -1.5 to 1.0V (-1.5V should give a 0V output and 1.0V should give a 5V output).

1. Identify V_2 as input voltage and V_1 as the reference voltage.
2. Let $\frac{R_F}{R_i} = 1$ and $V_{ref} = V_1 = -3$.

We obtain:

$$V_{out} = V_{in}(1 + \frac{R_f}{R_i}) - V_{ref}(\frac{R_f}{R_i})$$

$$V_{out} = V_2(1 + 1) - (-3)(1)$$

$$V_{out} = 2V_2 + 3$$

Plugging in $V_2 = -1.5$ gives $V_{out} = 0$ and $V_2 = 1$ gives $V_{out} = 5$.

6.2.5 Your uncalibrated sensor has a range of -2.5 to 2.5V (-2.5V should give a 0V output and 2.5V should give a 5V output).

The calibration cannot be done with this circuit. This is because for the input-output equations to hold, we would require a gain of 1 and an offset of 2.5.

If we identify V_1 as the reference voltage and V_2 as the input voltage, to get the required gain and offset, we would need to let $\frac{R_F}{R_i} = 0$. However, the offset will always be 0, and the 2.5 required cannot be achieved.

If we identify V_2 as the reference voltage and V_1 as the input voltage, to get the required gain and offset, we would need to let $\frac{R_F}{R_i} = -1$, which is physically impossible as resistances must be non-negative.

6.3 Q3: Control

6.3.1 If you want to control a DC motor to go to a desired position, describe how to form a digital input for each of the PID (Proportional, Integral, Derivative) terms.

- **Proportional term:** Set a desired position and read the current motor position through a motor encoder. Deduct the current motor position from the desired position to get the error in position. Multiply this error by a predefined K_D term to get the proportional digital input.
- **Integral term:** Add the error term from the current time-step with the summed errors from previous time-steps. Multiply this summed error by a predefined K_I term to get the integral digital input.
- **Derivative term:** Subtract the previous step's motor position from the current step's motor position and divide by the time-step. Multiply this term by a predefined K_D term to get the derivative digital input.

Add the proportional, integral, and derivative terms together to get the full digital input, and send the input to the motor controller.

6.3.2 If the system you want to control is sluggish, which PID term(s) will you use and why?

I would increase the P (proportional) term as it makes the system react more aggressively to errors, thus reducing sluggishness and decreasing the sluggishness of the system.

6.3.3 After applying the control in the previous question, if the system still has significant steady-state error, which PID term(s) will you use and why?

I would increase the I (integral) term as it accumulates past errors when there is a steady-state error. This would cause the integral term to keep increasing until the error is driven to zero.

6.3.4 After applying the control in the previous question, if the system still has overshoot, which PID term(s) will you apply and why?

I would increase the D (derivative) term as it acts as a damping term and makes the response less aggressive while still maintaining a reasonably fast reaction.